

Compilers and Formal Languages (8)

Email: christian.urban at kcl.ac.uk
Office Hours: Thursdays 12 – 14
Location: N7.07 (North Wing, Bush House)
Slides & Progs: KEATS (also homework is there)

Stmt ::= skip
| *Id* := *AExp*
| if *BExp* then *Block* else *Block*
| while *BExp* do *Block*
| read *Id*
| write *Id*
| write *String*

Stmts ::= *Stmt* ; *Stmts*
| *Stmt*


Block ::= { *Stmts* }
| *Stmt*

AExp ::= ...

BExp ::= ...

Compiling AExps

For example $1 + ((2 * 3) + (4 - 3))$:



ldc 1

ldc 2

ldc 3

imul

ldc 4

ldc 3

isub

iadd

iadd

Traverse tree in post-order \Rightarrow code for stack-machine

Compiling AExps

$compile(n, E) \stackrel{\text{def}}{=} \text{ldc } n$

$compile(a_1 + a_2, E) \stackrel{\text{def}}{=} compile(a_1, E) @ compile(a_2, E) @ \text{iadd}$

$compile(a_1 - a_2, E) \stackrel{\text{def}}{=} compile(a_1, E) @ compile(a_2, E) @ \text{isub}$

$compile(a_1 * a_2, E) \stackrel{\text{def}}{=} compile(a_1, E) @ compile(a_2, E) @ \text{imul}$

$compile(a_1 \setminus a_2, E) \stackrel{\text{def}}{=} compile(a_1, E) @ compile(a_2, E) @ \text{idiv}$

$compile(x, E) \stackrel{\text{def}}{=} \text{iload } E(x)$

Compiling Ifs

For example

```
if 1 = 1 then x := 2 else y := 3
```

```
ldc 1  
ldc 1  
if_icmpne L_ifelse  
ldc 2  
istore 0  
goto L_ifend  
L_ifelse: ←  
ldc 3  
istore 1  
L_ifend: ←
```

Compiling Whiles

For example

```
while x <= 10 do x := x + 1
```

```
L_wbegin:      ←  
    iload 0  
    ldc 10  
    if_icmpgt L_wend  
    iload 0  
    ldc 1  
    iadd  
    istore 0  
    goto L_wbegin  
L_wend:      ←
```

Compiling Writes

```
.method public static write(I)V
  .limit locals 1
  .limit stack 2
  getstatic java/lang/System/out
                                     Ljava/io/PrintStream;
  iload 0
  invokevirtual java/io/PrintStream/println(I)V
  return
.end method
```

```
iload  $E(x)$ 
invokestatic XXX/XXX/write(I)V
```

Compiling Main

```
.class public XXX.XXX
.super java/lang/Object

.method public <init>()V
    aload_0
    invokevirtual java/lang/Object/<init>()V
    return
.end method

.method public static main([Ljava/lang/String;)V
    .limit locals 200
    .limit stack 200

    ...here comes the compiled code...

    return
.end method
```


Functional Programming

```
def fib(n) = if n == 0 then 0
             else if n == 1 then 1
                 else fib(n - 1) + fib(n - 2);
```

```
def fact(n) = if n == 0 then 1 else n * fact(n - 1);
```

```
def ack(m, n) = if m == 0 then n + 1
                 else if n == 0 then ack(m - 1, 1)
                     else ack(m - 1, ack(m, n - 1));
```

```
def gcd(a, b) = if b == 0 then a else gcd(b, a % b);
```

Fun-Grammar

$Exp ::= Var \mid Num$
 $\mid Exp + Exp \mid \dots \mid (Exp)$
 $\mid \text{if } BExp \text{ then } Exp \text{ else } Exp$
 $\mid \text{write } Exp$
 $\mid Exp ; Exp \mid FunName (Exp, \dots, Exp)$

$BExp ::= \dots$

$Def ::= \text{def } FunName (x_1, \dots, x_n) = Exp$

$Prog ::= Def ; Prog \mid Exp ; Prog \mid Exp$

Abstract Syntax Trees

```
abstract class Exp
```

```
abstract class BExp
```

```
abstract class Decl
```

```
case class Var(s: String) extends Exp
```

```
case class Num(i: Int) extends Exp
```

```
case class Aop(o: String, a1: Exp, a2: Exp) extends Exp
```

```
case class If(a: BExp, e1: Exp, e2: Exp) extends Exp
```

```
case class Write(e: Exp) extends Exp
```

```
case class Sequ(e1: Exp, e2: Exp) extends Exp
```

```
case class Call(name: String, args: List[Exp]) extends Exp
```

```
case class Bop(o: String, a1: Exp, a2: Exp) extends BExp
```

```
case class Def(name: String,  
              args: List[String],  
              body: Exp) extends Decl
```

```
case class Main(e: Exp) extends Decl
```

Ideas

Use separate JVM methods for each Fun-function.

Compile `exp` such that the result of the expression is on top of the stack.

- `write(1 + 2)`
- `1 + 2; 3 + 4`

Sequences

Compiling `exp1 ; exp2`:

```
compile(exp1)
```

```
pop
```

```
compile(exp2)
```

Write

Compiling call to write(1+2):

```
compile(1+2)
```

```
dup
```

```
invokestatic XXX/XXX/write(I)V
```

needs the helper method

```
.method public static write(I)V
```

```
  .limit locals 1
```

```
  .limit stack 2
```

```
  getstatic java/lang/System/out Ljava/io/PrintStream;
```

```
  iload 0
```

```
  invokevirtual java/io/PrintStream/println(I)V
```

```
  return
```

```
.end method
```

Function Definitions

```
.method public static write(I)V
  .limit locals 1
  .limit stack 2
  getstatic java/lang/System/out Ljava/io/PrintStream;
  iload 0
  invokevirtual java/io/PrintStream/println(I)V
  return
.end method
```

We will need methods for definitions like

```
def fname (x1, ... , xn) = ...
```

```
.method public static fname (I...I)I
  .limit locals ??
  .limit stack ??
  ??
.end method
```

Stack Estimation

$estimate(n)$

$\stackrel{\text{def}}{=} 1$

$estimate(x)$

$\stackrel{\text{def}}{=} 1$

$estimate(a_1 \text{ aop } a_2)$

$\stackrel{\text{def}}{=} estimate(a_1) + estimate(a_2)$

$estimate(\text{if } b \text{ then } e_1 \text{ else } e_2)$

$\stackrel{\text{def}}{=} estimate(b) +$
 $max(estimate(e_1), estimate(e_2))$

$estimate(\text{write}(e))$

$\stackrel{\text{def}}{=} estimate(e) + 1$

$estimate(e_1; e_2)$

$\stackrel{\text{def}}{=} max(estimate(e_1), estimate(e_2))$

$estimate(f(e_1, \dots, e_n))$

$\stackrel{\text{def}}{=} \sum_{i=1..n} estimate(e_i)$

$estimate(a_1 \text{ bop } a_2)$

$\stackrel{\text{def}}{=} estimate(a_1) + estimate(a_2)$

Successor Function

```
.method public static suc(I)I
.limit locals 1
.limit stack 2
  iload 0
  ldc 1
  iadd
  ireturn
.end method
```

```
def suc(x) = x + 1;
```

Addition Function

```
.method public static add(II)I
.limit locals 2
.limit stack 5
  iload 0
  ldc 0
  if_icmpne If_else
  iload 1
  goto If_end
If_else:
  iload 0
  ldc 1
  isub
  iload 1
  invokestatic XXX/XXX/add(II)I
  invokestatic XXX/XXX/suc(I)I
If_end:
  ireturn
.end method
```

```
def add(x, y) =
  if x == 0 then y
  else suc(add(x - 1, y));
```

Factorial

```
.method public static fact(II)I
.limit locals 2
.limit stack 6
  iload 0
  ldc 0^^I
  if_icmpne If_else_2
  iload 1
  goto If_end_3
If_else_2:
  iload 0
  ldc 1
  isub
  iload 0
  iload 1
  imul
  invokestatic fact/fact/fact(II)I
If_end_3:
  ireturn
.end method
```

```
def fact(n, acc) =
  if n == 0 then acc
  else fact(n - 1, n * acc);
```

```
.method public static fact(II)I
```

```
.limit locals 2
```

```
.limit stack 6
```

```
fact_Start:
```

```
  iload 0
```

```
  ldc 0
```

```
  if_icmpne If_else_2
```

```
  iload 1
```

```
  goto If_end_3
```

```
If_else_2:
```

```
  iload 0
```

```
  ldc 1
```

```
  isub
```

```
  iload 0
```

```
  iload 1
```

```
  imul
```

```
  istore 1
```

```
  istore 0
```

```
  goto fact_Start
```

```
If_end_3:
```

```
  ireturn
```

```
def fact(n, acc) =  
  if n == 0 then acc  
  else fact(n - 1, n * acc);
```

Tail Recursion

A call to $f(\text{args})$ is usually compiled as

```
args onto stack  
invokestatic .../f
```

Tail Recursion

A call to $f(\text{args})$ is usually compiled as

```
args onto stack  
invokestatic .../f
```

A call is in tail position provided:

- if B_{exp} then `Exp` else `Exp`
- $\text{Exp} ; \text{Exp}$
- Exp op Exp

then a call $f(\text{args})$ can be compiled as

```
prepare environment  
jump to start of function
```

Tail Recursive Call

```
def compile_expT(a: Exp, env: Mem, name: String): Instrs =  
  ...  
  case Call(n, args) => if (name == n)  
  {  
    val stores =  
      args.zipWithIndex.map { case (x, y) => i"istore $y" }  
  
    args.map(a => compile_expT(a, env, "")).mkString ++  
    stores.reverse.mkString ++  
    i"goto ${n}_Start"  
  } else {  
    val is = "I" * args.length  
    args.map(a => compile_expT(a, env, "")).mkString ++  
    i"invokestatic XXX/XXX/${n}(${is})I"  
  }
```

Dijkstra on Testing

“Program testing can be a very effective way to show the presence of bugs, but it is hopelessly inadequate for showing their absence.”

What is good about compilers: the either seem to work, or go horribly wrong (most of the time).

Proving Programs to be Correct

Theorem: There are infinitely many prime numbers.

Proof ...

similarly


Theorem: The program is doing what it is supposed to be doing.

Long, long proof ...

This can be a gigantic proof. The only hope is to have help from the computer. 'Program' is here to be understood to be quite general (compiler, OS, ...).

Can This Be Done?

- in 2008, verification of a small C-compiler
 - “if my input program has a certain behaviour, then the compiled machine code has the same behaviour”
 - is as good as gcc -O1, but much, much less buggy



Fuzzy Testing C-Compilers

- tested GCC, LLVM and others by randomly generating C-programs
- found more than 300 bugs in GCC and also many in LLVM (some of them highest-level critical)
- about CompCert:

“The striking thing about our CompCert results is that the middle-end bugs we found in all other compilers are absent. As of early 2011, the under-development version of CompCert is the only compiler we have tested for which Csmith cannot find wrong-code errors. This is not for lack of trying: we have devoted about six CPU-years to the task.”

Register to Vote by Tuesday 26th November!

The UK General Election is on Thursday 12th December

Make sure you are registered vote by going online: <https://www.gov.uk/register-to-vote> - it takes 5 minutes!

You can register to vote if you are 18 years old or over, and:

- a UK or Irish citizen
- a qualifying Commonwealth citizen living in the UK
- an EU citizen living in the UK

For more information from KCLSU go to:

<https://www.kclsu.org/news/article/6015/Registered-to-Vote-If-not-get-on-it/>

