

Compilers and Formal Languages

Email: christian.urban at kcl.ac.uk

Office Hour: Thursdays 15 – 16

Location: N7.07 (North Wing, Bush House)

Slides & Progs: KEATS

Pollev: <https://pollev.com/cfltutoratki576>

1 Introduction, Languages	6 While-Language
2 Regular Expressions, Derivatives	7 Compilation, JVM
3 Automata, Regular Languages	8 Compiling Functional Languages
4 Lexing, Tokenising	9 Optimisations
5 Grammars, Parsing	10 LLVM

```
.method public static main([Ljava/lang/String;)V
    .limit locals 200
    .limit stack 200
    invokestatic foo/foo/read()I
    istore 0
    ldc 1
    istore 1
Loop_begin_4:
    iload 0
    ldc 0
    if_icmple Loop_end_5
    iload 0
    iload 1
    imul
    istore 1
    iload 0
    ldc 1
    isub
    istore 0
    goto Loop_begin_4
Loop_end_5:
    iload 1
    invokestatic foo/foo/write(I)V
    return
.end method
```

```
.method public static main([Ljava/lang/String;)V
    .limit locals 200
    .limit stack 200
    invokestatic foo/foo/read()I
    istore 0          ; n
    ldc 1
    istore 1          ; res
Loop_begin_4:
    iload 0          ; n
    ldc 0
    if_icmple Loop_end_5
    iload 0          ; n
    iload 1          ; res
    imul
    istore 1          ; res
    iload 0          ; n
    ldc 1
    isub
    istore 0          ; n
    goto Loop_begin_4
Loop_end_5:
    iload 1          ; res
    invokestatic foo/foo/write(I)V
    return
.end method
```

```

def mkeps(r: Rexp) : Val = r match {
    ...
    case PLUS(r) => Stars(List(mkeps(r)))
    case OPTIONAL(r) => Stars(Nil)
    case NTIMES(r, n) => Stars(List.fill(n)(mkeps(r)))
}

def inj(r: Rexp, c: Char, v: Val) : Val = (r, v) match {
    ...
    case (RANGE(_), Empty) => Chr(c)
    case (PLUS(r), Sequ(v1, Stars(vs))) => Stars(inj(r, c, v1)::vs)
    case (OPTIONAL(r), v) => Stars(inj(r, c, v)::Nil)
    case (NTIMES(r, n), Sequ(v1, Stars(vs))) => Stars(inj(r, c, v1)::vs)
}

```

$r^? \stackrel{\text{def}}{=} r^{\{0..1\}}$

Functional Programming

```
def fib(n) = if n == 0 then 0
             else if n == 1 then 1
             else fib(n - 1) + fib(n - 2);

def fact(n) = if n == 0 then 1 else n * fact(n - 1);

def ack(m, n) = if m == 0 then n + 1
                 else if n == 0 then ack(m - 1, 1)
                 else ack(m - 1, ack(m, n - 1));

def gcd(a, b) = if b == 0 then a else gcd(b, a % b);
```

Fun-Grammar

Exp ::= *Var* | *Num*

| *Exp* + *Exp* | ... | (*Exp*)

| if *BExp* then *Exp* else *Exp*

| write *Exp*

| *Exp* ; *Exp* | *FunName* (*Exp*, ..., *Exp*)

BExp ::= ...

Def ::= def *FunName* (x_1, \dots, x_n) = *Exp*

Prog ::= *Def* ; *Prog* | *Exp* ; *Prog* | *Exp*

Abstract Syntax Trees

```
abstract class Exp
abstract class BExp
abstract class Decl

case class Var(s: String) extends Exp
case class Num(i: Int) extends Exp
case class Aop(o: String, a1: Exp, a2: Exp) extends Exp
case class If(a: BExp, e1: Exp, e2: Exp) extends Exp
case class Write(e: Exp) extends Exp
case class Sequ(e1: Exp, e2: Exp) extends Exp
case class Call(name: String, args: List[Exp]) extends Exp

case class Bop(o: String, a1: Exp, a2: Exp) extends BExp

case class Def(name: String,
               args: List[String],
               body: Exp) extends Decl
case class Main(e: Exp) extends Decl
```

Ideas

Use separate JVM methods for each Fun-function.

Compile `exprs` such that the result of the expression
is on top of the stack.

- `write(1 + 2)`
- `1 + 2; 3 + 4`

Sequences

Compiling exp1 ; exp2:

```
compile(exp1)
```

```
pop
```

```
compile(exp2)
```

Write

Compiling call to write(1+2):

```
compile(1+2)
dup
invokestatic XXX/XXX/write(I)V
```

needs the helper method

```
.method public static write(I)V
    .limit locals 1
    .limit stack 2
    getstatic java/lang/System/out Ljava/io/PrintStream;
    iload 0
    invokevirtual java/io/PrintStream/println(I)V
    return
.end method
```

Function Definitions

```
.method public static write(I)V
    .limit locals 1
    .limit stack 2
    getstatic java/lang/System/out Ljava/io/PrintStream;
    iload 0
    invokevirtual java/io/PrintStream/println(I)V
    return
.end method
```

We will need methods for definitions like

```
def fname (x1, ... , xn) = ...
```

```
.method public static fname (I...I)
    .limit locals ???
    .limit stack ???
    ??
.end method
```

Stack Estimation

$\text{estimate}(n)$	$\stackrel{\text{def}}{=} 1$
$\text{estimate}(x)$	$\stackrel{\text{def}}{=} 1$
$\text{estimate}(a_1 \text{ aop } a_2)$	$\stackrel{\text{def}}{=} \text{estimate}(a_1) + \text{estimate}(a_2)$
$\text{estimate}(\text{if } b \text{ then } e_1 \text{ else } e_2)$	$\stackrel{\text{def}}{=} \text{estimate}(b) + \max(\text{estimate}(e_1), \text{estimate}(e_2))$
$\text{estimate}(\text{write}(e))$	$\stackrel{\text{def}}{=} \text{estimate}(e) + 1$
$\text{estimate}(e_1; e_2)$	$\stackrel{\text{def}}{=} \max(\text{estimate}(e_1), \text{estimate}(e_2))$
$\text{estimate}(f(e_1, \dots, e_n))$	$\stackrel{\text{def}}{=} \sum_{i=1..n} \text{estimate}(e_i)$
$\text{estimate}(a_1 \text{ bop } a_2)$	$\stackrel{\text{def}}{=} \text{estimate}(a_1) + \text{estimate}(a_2)$

Successor Function

```
.method public static suc(I)I  
.limit locals 1  
.limit stack 2  
    iload 0  
    ldc 1  
    iadd  
    ireturn  
.end method
```

```
def suc(x) = x + 1;
```

Addition Function

```
.method public static add(II)I
.limit locals 2
.limit stack 5
    iload 0
    ldc 0
    if_icmpne If_else
    iload 1
    goto If_end
If_else:
    iload 0
    ldc 1
    isub
    iload 1
    invokestatic XXX/XXX/add(II)I
    invokestatic XXX/XXX/suc(I)I
If_end:
    ireturn
.end method
```

```
def add(x, y) =
    if x == 0 then y
    else suc(add(x - 1, y));
```

Factorial

```
.method public static fact(II)I
.limit locals 2
.limit stack 6
    iload 0
    ldc 0
    if_icmpne If_else_2
    iload 1
    goto If_end_3
If_else_2:
    iload 0
    ldc 1
    isub
    iload 0
    iload 1
    imul
    invokestatic fact/fact/fact(II)I
If_end_3:
    ireturn
.end method
```

```
def fact(n, acc) =
    if n == 0 then acc
    else fact(n - 1, n * acc);
```

```
.method public static fact(II)I  
.limit locals 2  
.limit stack 6
```

```
fact_Start:
```

```
    iload 0  
    ldc 0  
    if_icmpne If_else_2  
    iload 1  
    goto If_end_3
```

```
If_else_2:
```

```
    iload 0  
    ldc 1  
    isub  
    iload 0  
    iload 1  
    imul
```

```
    istore 1
```

```
    istore 0
```

```
    goto fact_Start
```

```
def fact(n, acc) =  
    if n == 0 then acc  
    else fact(n - 1, n * acc);
```

```
If_end_3:
```

Tail Recursion

A call to `f(args)` is usually compiled as

```
args onto stack  
invokestatic .../f
```

Tail Recursion

A call to $f(\text{args})$ is usually compiled as

```
args onto stack  
invokestatic .../f
```

A call is in tail position provided:

- if $B\text{exp}$ then Exp else Exp
- Exp ; Exp
- Exp op Exp

then a call $f(\text{args})$ can be compiled as

```
prepare environment  
jump to start of function
```

Tail Recursive Call

```
def compile_expT(a: Exp, env: Mem, name: String): Instrs =  
...  
case Call(n, args) => if (name == n)  
{  
    val stores =  
        args.zipWithIndex.map { case (x, y) => i"istore $y" }  
  
    args.map(a => compile_expT(a, env, "")).mkString ++  
    stores.reverse.mkString ++  
    i"goto ${n}_Start"  
} else {  
    val is = "I" * args.length  
    args.map(a => compile_expT(a, env, "")).mkString ++  
    i"invokestatic XXX/XXX/${n}(${is})I"  
}
```

Dijkstra on Testing

“Program testing can be a very effective way to show the presence of bugs, but it is hopelessly inadequate for showing their absence.”

What is good about compilers: they either seem to work, or go horribly wrong (most of the time).

Proving Programs to be Correct

Theorem: There are infinitely many prime numbers.

Proof ...

similarly


Theorem: The program is doing what it is supposed to be doing.

Long, long proof ...

This can be a gigantic proof. The only hope is to have help from the computer. ‘Program’ is here to be understood to be quite general (compiler, OS,).

Can This Be Done?

- in 2008, verification of a small C-compiler
 - “if my input program has a certain behaviour, then the compiled machine code has the same behaviour”
 - is as good as gcc -O1, but much, much less buggy



Fuzzy Testing C-Compilers

- tested GCC, LLVM and others by randomly generating C-programs
- found more than 300 bugs in GCC and also many in LLVM (some of them highest-level critical)
- about CompCert:

“The striking thing about our CompCert results is that the middle-end bugs we found in all other compilers are absent. As of early 2011, the under-development version of CompCert is the only compiler we have tested for which Csmith cannot find wrong-code errors. This is not for lack of trying: we have devoted about six CPU-years to the task.”

