

# PEP Scala (4)

Email: christian.urban at kcl.ac.uk

Office: N7.07 (North Wing, Bush House)

Slides & Code: KEATS

Office Hours: Thursdays 12:00 – 14:00

Additionally: (for Scala) Tuesdays 10:45 – 11:45

# PEP Scala (4)

Email: christian.urban at kcl.ac.uk

Office: N7.07 (North Wing, Bush House)

Slides & Code: KEATS

A Crash-Course in Scala

Office Hours: Thursdays 12:00 – 14:00

Additionally: (for Scala) Tuesdays 10:45 – 11:45

# Hints in CW

## Hints

**For Preliminary Part:** useful operations involving regular expressions:

```
reg.findAllIn(s).toList
```

finds all substrings in s according to a regular regular expression reg; useful list operations: .distinct removing duplicates from a list, .count counts the number of elements in a list that satisfy some condition, .toMap transfers a list of pairs into a Map, .sum adds up a list of integers, .max calculates the maximum of a list.

**For Core Part:** use .split(",").toList for splitting strings according to commas (similarly \n), .getOrElse(...,...) allows to query a Map, but also gives a default value if the Map is not defined, a Map can be 'updated' by using +, .contains and .filter can test whether an element is included in a list, and respectively filter out elements in a list, .sortBy(\_.\_2) sorts a list of pairs according to the second elements in the pairs—the sorting is done from smallest to highest, .take(n) for taking some elements in a list (takes fewer if the list contains less than n elements).

- Scala Library, e.g. span in

[https://www.scala-lang.org/api/current/scala/  
collection/immutable>List.html](https://www.scala-lang.org/api/current/scala/collection/immutable>List.html)

# Preliminary 7

Raw marks (261 submissions):

- 4%: 236
- 3%: 10
- 2%: 1
- 1%: 0
- 0%: 15

(interviews ongoing!)

```
def is_legal(dim: Int, p: Path, x: Pos) = {
    if (...some_really_long_condition...) false
    else true
}
```

```
def is_legal(dim: Int, p: Path, x: Pos) = {
    if (...some_really_long_condition...) false
    else true
}
```

---

```
def is_legal(dim: Int, p: Path, x: Pos) =
  !(...some_really_long_condition...)
```

```
def foobar(...) = {  
    val cs = for (c <- str) yield c.toLowerCase  
    ...  
}
```

```
def foobar(...) = {  
    val cs = for (c <- str) yield c.toLowerCase  
    ...  
}
```

---

```
def foobar(...) = {  
    val cs = str.map(_.toLowerCase)  
    ...  
}
```

```
def RomanNumeral2Int(rs: RomanNumeral): Int =  
  rs match {  
    case Nil => 0  
    case M::r    => 1000 + RomanNumeral2Int(r)  
    case C::M::r => 900 + RomanNumeral2Int(r)  
    case D::r    => 500 + RomanNumeral2Int(r)  
    case C::D::r => 400 + RomanNumeral2Int(r)  
    case C::r    => 100 + RomanNumeral2Int(r)  
    case X::C::r => 90 + RomanNumeral2Int(r)  
    case L::r    => 50 + RomanNumeral2Int(r)  
    case X::L::r => 40 + RomanNumeral2Int(r)  
    case X::r    => 10 + RomanNumeral2Int(r)  
    case I::X::r => 9 + RomanNumeral2Int(r)  
    case V::r    => 5 + RomanNumeral2Int(r)  
    case I::V::r => 4 + RomanNumeral2Int(r)  
    case I::r    => 1 + RomanNumeral2Int(r)  
  }
```

# Last Week: Pattern Matching

```
def fizz_buzz(n: Int) : String =  
  (n % 3, n % 5) match {  
    case (0, 0) => "fizz buzz"  
    case (0, _) => "fizz"  
    case (_, 0) => "buzz"  
    case _ => n.toString  
  }
```

# Reverse Polish Notation

$$(3 + 1) * (2 + 9)$$

$\Rightarrow$

3 1 + 2 9 + \*

# Reverse Polish Notation

$$(3 + 1) * (2 + 9)$$

$\Rightarrow$

3 1 + 2 9 + \*

ldc 3

ldc 1

iadd

ldc 2

ldc 9

iadd


imul

# Sudoku


A very simple-minded version on 110 problems:

- 1 core: 800 secs
- 2 cores: 400 secs
- 8 cores: 290 secs
- 18 cores: 142 secs


# DFAs



# DFAs




# DFAs




**a**

# DFAs




*ab*

# DFAs




*aba*

# DFAs



*abaa*

# DFAs



*abaaa*  $\Rightarrow$  yes

# DFAs


A **deterministic finite automaton**, DFA, consists of 5 things:

- an alphabet  $\Sigma$
- a set of states  $Q_s$
- one of these states is the start state  $Q_0$
- some states are accepting states  $F$ , and
- there is transition function  $\delta$

which takes a state and a character as arguments and produces a new state; this function might not be everywhere defined

$$A(\Sigma, Q_s, Q_0, F, \delta)$$

# NFAs





# Mind-Blowing Regular Expressions: in Python, JavaScript, Java

# Regular Expressions

Suppose you have a regular expression  $(a^*)b$ :

”aaaaaaaaaaaaab”

# Regular Expressions

Suppose you have a regular expression  $(a^*)b$ :

”aaaaa.....aaaaaaaaaaaaaaaaaaab”

# Regular Expressions

Suppose you have a regular expression  $(a^*)b$ :

“aaaaa.....aaaaaaaaaaaaaaaaaa”

# Regular Expressions

Suppose you have a regular expression  $(a^*)^*b$ :

”aaaaa.....aaaaaaaaaaaaaaaaaaab”

# Regular Expressions

Suppose you have a regular expression  $(a^*)^*b$ :

”aaaaa.....aaaaaaaaaaaaaaaaaa”

# Regular Expressions



Suppose you have a regular expression  $(a^*)^*b$ :

”aaaaa.....aaaaaaaaaaaaaaaaaa”

How long does Python need to find out?

# CW 9: Regexes

Graphs:  $(a^*)^*b$  and strings  $\underbrace{a \dots a}_n$



$\cdot 10^6$

<https://vimeo.com/112065252>

# **Register to Vote by Tuesday 26<sup>th</sup> November!**

**The UK General Election is on Thursday 12<sup>th</sup> December**

**Make sure you are registered vote by going online: <https://www.gov.uk/register-to-vote> - it takes 5 minutes!**

**You can register to vote if you are 18 years old or over, and:**

- a UK or Irish citizen**
- a qualifying Commonwealth citizen living in the UK**
- an EU citizen living in the UK**

**For more information from KCLSU go to:**

**<https://www.kclsu.org/news/article/6015/Registered-to-Vote-If-not-get-on-it/>**

