

Access Control and Privacy Policies (1)





Email: christian.urban at kcl.ac.uk
Office: S1.27 (1st floor Strand Building)
Slides: KEATS



Security Engineers

According to Bruce Schneier, **security engineers** require a particular **mindset**:

"Security engineers — at least the good ones — see the world differently. They can't walk into a store without noticing how they might shoplift. They can't use a computer without wondering about the security vulnerabilities. They can't vote without trying to figure out how to vote twice. They just can't help it."



Chip-and-PIN



- Chip-and-PIN was introduced in the UK in 2004
- before that customers had to sign a receipt
- Is Chip-and-PIN a more secure system?

(Some other countries still use the old method.)

Yes ...

"Chip-and-PIN is so effective in this country [UK] that fraudsters are starting to move their activities overseas," said Emile Abu-Shakra, spokesman for Lloyds TSB (in the *Guardian*, 2006).

- mag-stripe cards cannot be cloned anymore
- stolen or cloned cards need to be used abroad
- fraud on lost, stolen and counterfeit credit cards was down £60m (24%) on 2004's figure

But let's see ...



Bank



customer / you

But let's see ...




Bank




customer / you

But let's see ...



But let's see ...



Chip-and-PIN

- A “tamperesitant” terminal playing Tetris on [youtube](http://www.youtube.com/watch?v=wWTzkD9M0sU).


(<http://www.youtube.com/watch?v=wWTzkD9M0sU>)





Chip-and-PIN

- in 2006, Shell petrol stations stopped accepting Chip-and-PIN after £1m had been stolen from customer accounts
- in 2008, hundreds of card readers for use in Britain, Ireland, the Netherlands, Denmark, and Belgium had been expertly tampered with shortly after manufacture so that details and PINs of credit cards were sent during the 9 months before over mobile phone networks to criminals in Lahore, Pakistan

Chip-and-PIN is Broken




- man-in-the-middle attacks by the group around Ross Anderson




on BBC Newsnight
in 2010 or [youtube](#)

Chip-and-PIN is Really Broken




- same group successfully attacked this year card readers and ATM machines
- the problem: several types of ATMs generate poor random numbers, which are used as nonces

The Problem ...



- the burden of proof for fraud and financial liability was shifted to the customer

Screwed Again




- **Responsibility**

"You understand that you are financially responsible for all uses of RBS Secure."

https://www.rbssecure.co.uk/rbs/tdsecure/terms_of_use.jsp

Web Applications




Servers from
Dot.com Inc.



Client(s)


- What are pitfalls and best practices?

Web Applications




- What are pitfalls and best practices?

Web Applications



- What are pitfalls and best practices?

Web Applications



- What are pitfalls and best practices?

Scala + Play

a simple response from the server:


```
1 package controllers
2 import play.api.mvc._
3
4 object Application extends Controller {
5
6     // answering a GET request
7     val index = Action { request =>
8         Ok("Hello world!")
9     }
10 }
```

alternative response:

```
Ok("<H1>Hello world!</H1>").as(HTML)
```

```
1 object Application extends Controller {
2
3   // GET request -> present login form
4   val index = Action { request =>
5
6     val form =
7       """<form method="post">
8         Login: <input type="text" name="login"><br>
9         Password: <input type="password" name="password"><br>
10        <input type="submit"></form>"""
11
12     Ok(form).as(HTML)
13   }
14
15   // POST data: processing the login data
16   val receive = Action { request =>
17
18     val form_data = Form (tuple ("login" -> text, "password" -> text))
19
20     val (login, password) = form_data.bindFromRequest()(request).get
21
22     Ok("Received login: " + login + " and password: " + password)
23   }
24 }
```

Cookies




Servers from
Dot.com Inc.

GET request



Client

Cookies



Servers from
Dot.com Inc.

GET request




read a cookie




Client

Cookies



Cookies



- cookies: max 4KB data
- cookie theft, cross-site scripting attacks
- session cookies, persistent cookies, HttpOnly cookies, third-party cookies, zombie cookies

Cookies

EU Privacy Directive about Cookies:

"In May 2011, a European Union law was passed stating that websites that leave non-essential cookies on visitors' devices have to alert the visitor and get acceptance from them. This law applies to both individuals and businesses based in the EU regardless of the nationality of their website's visitors or the location of their web host. It is not enough to simply update a website's terms and conditions or privacy policy. The deadline to comply with the new EU cookie law was 26th May 2012 and failure to do so could mean a fine of up to £500,000." →BBC News

- session cookies, persistent cookies, HttpOnly cookies, third-party cookies, zombie cookies

My First Webapp

GET request:

- 1 read the cookie from client
- 2 if none is present, set `visits` to **0**
- 3 if cookie is present, extract `visits` counter
- 4 if `visits` is greater or equal **10**,
print a valued customer message
otherwise just a normal message
- 5 increase `visits` by **1** and store new cookie with
client

```

1  object Application extends Controller {
2
3      def gt_cookie(c: Option[Cookie]) : Int = c.map(_.value) match {
4          case Some(s) if (s.forall(_.isDigit)) => s.toInt
5          case _ => 0
6      }
7
8      def mk_cookie(i: Int) : Cookie = {
9          Cookie("visits", i.toString)
10     }
11
12     // GET request: read cookie data first
13     def index = Action { request =>
14
15         val visits_cookie = request.cookies.get("visits")
16         val visits = gt_cookie(visits_cookie)
17
18         val msg1 = "You are a valued customer who has visited this site %d
19         val msg2 = "You have visited this site %d times."
20         val msg =
21             if (visits >= 10) msg1.format(visits) else msg2.format(visits)
22
23         //send with new cookie
24         Ok(msg).as(HTML).withCookies(mk_cookie(visits + 1))
25     }
26 }

```



- data integrity needs to be ensured

```
1  object Application extends Controller {
2
3    //SHA-1, SHA-256
4    def mk_hash(s: String) : String = {
5      val hash_fun = MessageDigest.getInstance("SHA-1")
6      hash_fun.digest(s.getBytes).map{ "%02x".format(_) }.mkString
7    }
8
9    def gt_cookie(c: Option[Cookie]) : Int =
10     c.map(_.value.split("/")) match {
11       case Some(Array(s, h))
12         if (s.forall(_.isDigit) && mk_hash(s) == h) => s.toInt
13       case _ => 0
14     }
15
16    def mk_cookie(i: Int) : Cookie = {
17      val s = i.toString
18      Cookie("visits", s + "/" + mk_hash(s))
19    }
20
21    def index = Action { request => ... }
22 }
```

- the counter/hash pair is intended to prevent tampering

SHA-1

- SHA-1 is a cryptographic hash function (MD5, SHA-256, SHA-512, ...)
- message \rightarrow digest
- no known attack exists, except brute force

SHA-1

- SHA-1 is a cryptographic hash function (MD5, SHA-256, SHA-512, ...)
- message \rightarrow digest
- no known attack exists, except brute force
- but dictionary attacks are very effective for extracting passwords (later)


```
1 object Application extends Controller {
2
3   val salt = "my secret key"
4
5   //SHA-1, SHA-256 + salt
6   def mk_hash(s: String) : String = {
7     val hash_fun = MessageDigest.getInstance("SHA-1")
8     hash_fun.digest((s + salt).getBytes).map{ "%02x".format(_) }.mkStr
9   }
10
11  def gt_cookie(c: Option[Cookie]) : Int =
12    c.map(_.value.split("/")) match {
13      case Some(Array(s, h))
14        if (s.forall(_.isDigit) && mk_hash(s) == h) => s.toInt
15      case _ => 0
16    }
17
18  def mk_cookie(i: Int) : Cookie = {
19    val s = i.toString
20    Cookie("visits", s + "/" + mk_hash(s))
21  }
22
23  def index = Action { request => ... }
24 }
```

should be random



Unix Passwords

- passwords are **not** stored in clear text

Password Blunders

in late 2009, when an SQL injection attack against online games service RockYou.com exposed 32 million plaintext passwords

1.3 million Gawker credentials exposed in December 2010 contained MD5 hashes

Web user maintains 25 separate accounts but uses just 6.5 passwords

Brute Forcing Passwords

- How fast can hackers crack SHA-1 passwords?

Brute Forcing Passwords

- How fast can hackers crack SHA-1 passwords?
- The answer is 2 billion attempts per second using a Radeon HD 7970

password length	time
5 letters	5 secs
6 letters	500 secs
7 letters	13 hours
8 letters	57 days
9 letters	15 years



graphics card
ca. £300

5 letters $\approx 100^5 = 10$ billion combinations
(1 letter - upper case, lower case, digits, symbols ≈ 100)

Passwords

- How do recover from a breakin?

This Course

- breakins (buffer overflows)
- access control (role based, data security / data integrity)
- protocols
- access control logic
- privacy

Scott McNealy:

"You have zero privacy anyway. *Get over it.*"

Homework

Thinking as a Defender

- What are we trying to protect?
- What properties are we trying to enforce?
- Who are the attackers? Capabilities?
Motivations?
- What kind of attack are we trying to protect?
- Who can fix any vulnerabilities?
- What are the weaknesses of the system?
- What will successful attacks cost us?
- How likely are the attacks?
- Security almost always is **not** free!

The Security Mindset

- How things can go wrong.
- Think outside the box.

The difference between a criminal is to only think about how things can go wrong.

Maps in Scala

- `map` takes a function, say `f`, and applies it to every element of the list:

```
List(1, 2, 3, 4, 5, 6, 7, 8, 9)
```

```
List(1, 4, 9, 16, 25, 36, 49, 64, 81)
```